

0716

# Snelkoppeling met slangpilaar, 3/4"(Q)



3/4" snelkoppeling met 3/4" slangpilaar.

# Technical Data

Item Number	0716
Koppeling maat	3/4 "
Materiaal	Verchromd messing
Meets the REACH Regulation (EC) No. 1907/2006	Yes **
California Proposition 65 Compliant	Nee
SCIP number	095b5bea-9314-4e2d-987b-8726dbd84c43
Gebruik van phtalaten en bisfenol a	Nee
Is Halal and Kosher compliant	Ja
Aantal per collo	10 Pcs.
Aantal per pallet (80 x 120 x 180-200 cm)	3180 Pcs.
Quantity Per Layer (Pallet)	0 Pcs.
Lengte	160 mm
Breedte	67 mm
Hoogte	50 mm
Netto gewicht	0,13 kg
Gewicht doos (Recycling symbol "20" PAP)	0,0118 kg
Tare total	0,0118 kg
Bruto gewicht	0,14 kg
Kubieke meter	0,000536 M3
Maximale reinigingstemperatuur (vaatwasser)	80 °C
Maximale gebruikstemperatuur (voor non food contact)	70 °C
Minimale gebruikstemperatuur <sup>3</sup>	-30 °C
Min. pH-value in usage concentration	2 pH
Maximale pH-waarde in gebruik	11 pH
Maximale druk Bar	25 Bar
GTIN-13 code	5705020007163
GTIN-14 code	15705020007160
Commodity code	74122000
Land van oorsprong	Denmark

The hose coupling on the hose and foaming gun have to be greased regularly to maintain the coupling ability on the equipment. The grease applied during mounting will be rinsed away by the water flow and thus needs to be renewed.

\*\* Lead (Pb, CAS: 7439-92-1) is on the REACH candidate list as a Substance of Very High Concern (SVHC). This product contains lead (Pb) in a concentration above 0.1% w/w. Consequently the REACH Regulation (EC) No. 1907/2006 require Vikan to notify our customers of the content of lead. This product is registered in the EU SCIP database. Please find SCIP number above.