

299152



Ergonomische alu steel m/
waterdoorvoer, slangpilaar,
Ø31 mm, 1560 mm, Zwart



Professionele steel met waterdoorvoer. Met geïsoleerde handgreep en slipvaste grip.

Technical Data

Item Number	299152
Materiaal	Geanodiseerd aluminium Polypropyleen Verchromd messing
Meets the REACH Regulation (EC) No. 1907/2006	Yes **
California Proposition 65 Compliant	Nee
SCIP number	e49c50b5-7653-429c-b8f3-803d37b5fetc
Gebruik van phtalaten en bisfenol a	Nee
Is Halal and Kosher compliant	Ja
Aantal per collo	10 Pcs.
Aantal per pallet (80 x 120 x 180-200 cm)	710 Pcs.
Quantity Per Layer (Pallet)	40 Pcs.
Product diameter	31 mm
Lengte	1560 mm
Breedte	31 mm
Hoogte	31 mm
Netto gewicht	0,58 kg
Gewicht doos (Recycling symbol "20" PAP)	0,03 kg
Tare total	0,03 kg
Bruto gewicht	0,61 kg
Kubieke meter	0,001499 M3
Maximale druk Bar	6 Bar
Maximale gebruikstemperatuur (voor non food contact)	80 °C
Min. pH-value in usage concentration	4 pH
Maximale pH-waarde in gebruik	11 pH
GTIN-13 code	5705022991019
GTIN-14 code	15705022991016
Commodity code	76169990
Land van oorsprong	Denmark

** Lead (Pb, CAS: 7439-92-1) is on the REACH candidate list as a Substance of Very High Concern (SVHC). This product contains lead (Pb) in a concentration above 0.1% w/w. Consequently the REACH Regulation (EC) No. 1907/2006 require Vikan to notify our customers of the content of lead. This product is registered in the EU SCIP database. Please find SCIP number above.